

# DC-DC轉換器快選表



DC-DC  
模塊型快選表

應用	系列		輸入電壓	輸出電壓	隔離電壓	工作溫度	尺寸 (長 x 寬 x 高 mm)	安規									
	圖片	類型															
LED 產業		LDD-300~700L	9~36V	2~32V	NA (非隔離)	-40 ~ +85°C	226 x 99 x 89	FCC/EAC/ CE/UKCA									
		LDD-300~700LW															
		LDD-300~700LS	9~32V	2~28V		25.4 x 10.5 x 9.3											
		LDB-300~350L	9~36V	2~40V		-40 ~ +70°C	31.8 x 20.3 x 12.2										
		LDB-300~350LW															
		LDB-500L	9~30V	2~32V													
		LDB-500LW															
		LDB-600L	9~28V	2~30V													
		LDB-600LW															
		LDDS-HW/HWB	12~56V	2~45V					-40 ~ +55°C	47 x 12 x 7	CE/EAC/ UKCA						
		LDD-1400H-DA	6~40V	3~36V					-40 ~ +85°C	40.6 x 23.5 x 10.1	CE/UKCA/ EAC/DALI						
		LDD-1400H-WDA															
		LDD-350~1050H-WDA	6~50V	3~45V													
		NLDD-350~1050H	10~56V (59V Max.)	6~52V								-40 ~ +50°C	32.1 x 20.5 x 12.5	CE/EAC/ UKCA			
		NLDD-350~1050HW															
		NLDD-1200~1400H		6~46V													
		NLDD-1200~1400HW															
		NHDD-40-100/100W	360~420V	350V											-30 ~ +40°C	32.1 x 20.5 x 12.5	CE/EAC/ UKCA
		LDH-25	9.5~32V	12.5~84V											-40 ~ +70°C	52.4 x 27.2 x 24	CE/EAC/ UKCA
		LDH-45	9~18V, 18~32V	12~126V											-40 ~ +70°C	75 x 53 x 22.7	CE/UKCA/ EAC/DALI
	LDH-65	9.5~32V	12.5~80V	-40 ~ +60°C	75 x 53 x 22.7			CE/EAC/ UKCA									